


Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE SEP 1986		2. REPORT TYPE		3. DATES COVERED 00-00-1986 to 00-00-1986	
4. TITLE AND SUBTITLE Computer Program: RCPWAVE				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U. S. Army Engineer Waterways Experiment Station,,Coastal Engineering Research Center,P. O. Box 631,Vicksburg,MS,39180				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT Same as Report (SAR)	18. NUMBER OF PAGES 2	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			



Coastal Engineering Technical Note



COMPUTER PROGRAM: RCPWAVE

PROGRAM PURPOSE: RCPWAVE is a numerical model for estimating the characteristics of waves as they propagate over arbitrary bathymetry.

BACKGROUND INFORMATION: The model simulates the propagation of linear, monochromatic waves by solving finite difference approximations of the model's governing equations at each grid cell of a mesh encompassing the area of interest. The equations represent the following aspects of linear wave theory: refraction, shoaling, diffraction due to very irregular bathymetry, and wave breaking. The model of Dally, Dean and Dalrymple (1984) is used to compute wave heights in the surf zone.

PROGRAM APPLICATION: The RCPWAVE model is typically applied in the following manner. An area of interest is defined and a Cartesian coordinate system is defined with the x-direction pointing in an offshore direction and the y-direction in an alongshore direction. A system of rectangular grid cells which encompasses the area is established by choosing constant grid cell dimensions in both coordinate directions which adequately resolve the bottom variations. Bottom bathymetry at the center of each grid cell must be digitized (usually from bathymetric charts) and entered into a disk file on computer. A second disk file is constructed; it contains the remaining input data which specify deep water wave parameters, grid cell dimensions, the number of grid cells, and parameters controlling the volume of printed output. Output is in the form of two-dimensional arrays of water depth, wave height, wave angle, wave length, and a breaker index which defines those cells where wave breaking is occurring.

PROGRAM ADVANTAGES AND DISADVANTAGES: The program is very inexpensive to apply. Presently, the simulation of one wave condition costs approximately four to five dollars on its host computer, the Control Data Corporation's (CDC) Cybernet system. The program requires very little input. The difficulty lies in selecting a grid system and digitizing the water depth data. Diffractive effects in the governing equations preclude the formation of caustics (wave ray crossing) and the necessity of having to interpret results at caustic locations. This is a problem with conventional wave ray propagation methods.

The program only treats monochromatic wave propagation using linear theory. A spectral representation of the wave climate is assumed to be

reasonably well simulated using a significant wave approach (use of the significant height, peak spectral period, and mean direction). The program cannot treat the effects of structures and therefore is limited to open coast applications or applications of a large scale where structural effects are not important.

ADDITIONAL INFORMATION: Program documentation and a user's manual are contained in WES Technical Report CERC-86-4 (Ebersole, Cialone, and Prater (1986)). Technical questions concerning application of the model can be directed to Bruce Ebersole, at (601) 634-3209, Bruce.A.Ebersole@erdc.usace.army.mil.

REFERENCES:

Dally, W. R. ., Dean, R. G., and Dalrymple, R. A. 1984. "Modeling Wave Transformation in the Surf Zone," Miscellaneous Paper CERC-84-8, U.S. Army Engineer Waterways Experiment Station, Vicksburg, MS.

Ebersole, B. A., Cialone, M. A., and Prater, M. D. 1986. "Regional Coastal Numerical Modeling System 1: RCPWAVE -- A Linear Wave Propagation Engineering Use," Technical Report CERC-86-4, U.S. Army Engineer Watersways Experiment Station, Vicksburg, MS.